

 **Scratch-free**
Industrial Scratch Resistant Coating

 **Protection against shards of glass**
In case of breakage, the glass is held together

 **Crystal clear**
The view is not distorted

 **EN 12600 certified**
International breakage certification

 **Security adhesive**
Considerably stronger than the adhesive of heat protection films

 **Manufacturer**
Commonwealth Laminating & Coating, USA

 **35 years of experience**
One of the longest-operating distributors in the industry

 **Long-term solution**
With a 10-year warranty

 **UV protection**
Protects your health and your valuables

Level of protection



Safety with window films!

Tensile strength 34900 psi 241 N/mm ²	Break strength 136 lbs/inch 24 N/mm	Puncture strength 93 lbs 414 N
--	---	--------------------------------------

	Single pane
Total Solar Energy Rejected	20%
Visible Light Transmitted	86%
Visible Light Reflected Exterior	10%
Total Solar Energy Reflected	8%
Total Solar Energy Absorbed	18%
Total Solar Energy Transmitted	74%
UV Rejection	99%
U-Value	5,96

 **Warranty**
10 years

 **Interior/exterior**
Interior

 **Certification**
EN12600 2B2

 **Thickness**
100 microns

 **Sizes available**
0,91×30 m, 1,22×30m,
1,52×30 m, 1,82×30 m

 **Adhesive**
Double security adhesive

 **Layers**
One

 **Scratch Resistant Coating**
2nd generation